

Product Information: Racing FSX 10W-60

Description

Racing FSX 10W-60 is a high quality, fully synthetic motor oil which is intended for use in high performance engines, operating under severe conditions. A blend of high quality synthetic base fluids and a tailored additive system provides exceptional wear performance and offers superb film strength at elevated operating temperatures. The product exhibits excellent control over sludge and high temperature deposits. The high-quality base fluid composition within the product delivers optimum thermal stability, superior anti-oxidant performance and very low evaporation rates, resistance to oil cavitation at high RPM's can be expected.

Applications

Racing FSX 10W-60 is recommended for turbo-charged and naturally aspirated petrol and diesel engines, for ordinary road use and motor sport use, where the original equipment manufacturer or engine builder recommends a lubricant of this quality, performance level and viscosity.

Performance Features

- Exceptional wear performance
- Control over sludge and high temperature deposits
- Protects from corrosion
- Superb film strength at elevated temperatures
- Optimum thermal stability
- Superior anti-oxidant performance
- Very low evaporation rates
- Resistance to oil cavitation

Performance Levels

- API SN/CF
- ACEA A3/B3, A3/B4
- BMW M Applications

Typical Data

Characteristic	Unit	Result	Method
Density @ 15.6°C	kg/l	0.860	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	160.1	ASTM D445
Kinematic Viscosity @ 100°C	cSt	23.1	ASTM D445
Viscosity Index		174	ASTM D2270
Flashpoint (Open)	°C	250	ASTM D92
Pour Point	°C	-42	ASTM D97
CCS @ -30°C	mPa•s	5200	ASTM D5293
Total Base Number	mg KOH/g	11.2	ASTM D2896

Figures based on average production values