

## Product Information: Select XL Motor Oils

### Description

Select XL Motor Oils are a range of very high-quality, low detergent/dispersant engine lubricants, formulated utilising highly refined mineral base stocks and carefully selected performance additives. The products exhibit excellent resistance to wear and corrosion, as well as control over piston deposits, soot and sludge. The products offer enhanced cold flow characteristics and display outstanding thermal and oxidative stability and resistance to foaming.

### Applications

Select XL Motor Oils are recommended primarily for naturally aspirated four stroke petrol and diesel engines found in classic passenger cars, motorcycles, commercial vehicles and tractors manufactured post 1960 up to the early 1970's or where a lubricant of this performance level and quality is specified by the original equipment manufacturer. Care should be taken to ensure that the correct viscosity is selected. Select XL 30 and 40 are suitable choices for diesel engines found in canal boats, watercraft and older generators.

### Performance Features

- Excellent protection against wear
- Protection against corrosion
- Thermally stable
- Enhanced cold flow characteristics
- Excellent foam control
- Resistant to oxidation
- Control over piston deposits, soot and sludge

### Performance Levels

API SD/CC

### Typical Data

Characteristic	Unit	XL 20W	XL 30	XL 40	XL 50
Density @ 15.6°C	kg/l	0.870	0.874	0.879	0.894
Kinematic Viscosity @ 40°C	cSt	59.7	96.0	144.0	224.0
Kinematic Viscosity @ 100°C	cSt	8.1	11.2	14.7	19.5
Viscosity Index		103	102	101	99
Flashpoint (Open)	°C	210	220	226	230
Pour Point	°C	-33	-30	-24	-19

Figures based on average production values