



Product Information: Powertech 2T

Description

Powertech 2T oil is high quality lubricant for 2 stroke engines. It has been formulated utilising the latest additive technology and high quality base oil components, to produce a product that guarantees good engine wear protection and cleanliness, reliable control against exhaust system blocking and reduction of exhaust smoke. Powertech 2T oil contains a hydrocarbon diluent which gives the product excellent self-mixing properties and can therefore be used in oil injection and premix systems.

Applications

Powertech 2T oil is suitable for use in either oil injection or premix systems in low to medium output motorcycles, it can also be used in a variety of other 2 stroke engines fitted to chainsaws, hedge cutters, lawnmowers, garden strimmer's and go-karts, where the original equipment manufacturer recommends a 2 stroke lubricant of this quality.

Performance Features

- Good self-mixing properties
- Excellent anti-wear protection
- Control against exhaust system blocking
- Maintains engine cleanliness
- Protection against piston & cylinder scuffing
- Reduced exhaust smoke

Performance Levels

JASO FB
ISO-L-EGB
API TC

Always refer to the original equipment manufacturers handbook for suitable mixing ratios and lubricant specification requirements

Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.872
Kinematic Viscosity @ 40°C	cSt	63.5
Kinematic Viscosity @ 100°C	cSt	9.1
Viscosity Index		120
Flashpoint (Closed)	°C	122
Pour Point	°C	-20
Colour		Red

Figures based on average production values