



Product Information: Limitless Ultra 4T 15W-50

Description

Limitless Ultra 4T 15W-50 is a high quality fully synthetic motorcycle lubricant, which is formulated to provide ultimate engine and gear performance for all kinds of modern bikes. Limitless Ultra 4T 15W-50 exhibits excellent wear protection and outstanding resistance to oxidation. The advanced additive package displays excellent control of sludge and engine deposits, as well as protection against rust and corrosion.

The enhanced friction control of this lubricant promotes smooth clutch engagement and gear changes, hence optimising performance. The naturally high viscosity index of the lubricant ensures excellent cold flow characteristics at start-up and superb film strength at high temperatures.

Applications

Limitless Ultra 4T 15W-40 is suitable for use in high performance air and water cooled four stroke motorcycle engines including those with integral gearboxes and wet clutches, where a lubricant of this quality, performance level and viscosity is specified by the original equipment manufacturer.

Performance Features

- Excellent wear protection
- Outstanding resistance to oxidation
- Excellent cold flow characteristics
- Control of sludge and engine deposits
- Enhanced friction control for smooth performance
- Protection against rust and corrosion

Performance Levels

API SL
JASO MA2

Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.868
Kinematic Viscosity @ 40°C	cSt	132
Kinematic Viscosity @ 100°C	cSt	19.3
Viscosity Index		167
Flashpoint (Closed)	°C	235
Pour Point	°C	-30

Figures based on average production values