



## Product Information: ATF 3403

### Description

ATF 3403 is a premium synthetic based automatic transmission fluid formulated to deliver ultimate performance under the most severe conditions. The fluid exhibits exceptional thermal and oxidative stability. The appropriate frictional properties ensure smooth and consistent shudder free operation over time. The fluid also offers excellent wear protection and shear stability as well as outstanding low temperature fluidity.

### Applications

ATF 3403 is intended for use in Mercedes Benz 5 speed transmissions, with or without controlled torque converter lock-up clutch, or where a fluid of this quality and performance level is required by the original equipment manufacturers recommendation.

### Performance Features

- Excellent thermal & oxidative stability
- Low temperature fluidity
- High shear stability
- Exceptional wear protection
- Smooth gear shifting
- Consistent operation over time

### Performance Levels

Mercedes Benz: 236.10  
Transmission type: Mercedes Benz 5G-Tronic 722.6

May also be used in service for previous Mercedes Benz automatic transmissions.

### Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.849
Kinematic Viscosity @ 40°C	cSt	34.5
Kinematic Viscosity @ 100°C	cSt	7.4
Viscosity Index		189
Flashpoint (Open)	°C	195
Pour Point	°C	-45
Colour		Red

Figures based on average production values