



Product Information: Ultra 15W/40

Description

Ultra 15W/40 is mixed fleet engine oil, incorporating high quality virgin mineral oils and performance additives, which make it suitable for use in a wide variety of diesel and petrol engine designs, including turbo charged versions. The product protects engine components from rust and corrosion, as well as providing high levels of engine cleanliness and anti-wear performance.

Applications

This product is intended for use in a range of vehicle and engine types, including commercial vehicles, buses, coaches, cars and vans, plant and construction machinery and agricultural machinery. It may also be used in some transmissions, hydraulic systems, PTOs, and compressors, where a lubricant of this viscosity and performance is recommended.

Performance Features

- Shear stability
- Protects against bore polishing
- Catalytic converter compatible
- Control of sludge and piston deposits
- Rust and corrosion protection
- Excellent handling of soot
- Protects against premature wear
- Thermally stable
- Resistant to oxidation

Performance Levels

- API: CG-4/CF-4/SJ
- ACEA: A3/B4 (2012)
- Mercedes Benz: 228.3
- MAN: 3275
- Mack: EO-L
- Volvo: VDS 2
- VW: 505.00

Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.882
Kinematic Viscosity @ 40°C	cSt	105
Kinematic Viscosity @ 100°C	cSt	14.5
Viscosity Index		142
Flashpoint (Closed)	°C	230
Pour Point	°C	-39

Figures based on average production values