



## Product Information: ATF Dexron VI

### Description

This unique fluid is specially formulated to provide twice the service life of ATF Dexron III and offers enhanced performance for both new and older transmissions. It is designed to protect transmissions through improved oxidation resistance, friction durability, shear stability and wear protection.

The fluid delivers outstanding resistance against sludge and deposit formation, improved thermal stability, enhanced foam control and excellent low temperature fluidity. The shear stable formulation offers consistent shifting performance and eliminates transmission shudder.

### Applications

Intended for use in passenger car and commercial vehicles where a transmission fluid of this quality is required or where long product service life and enhanced performance is required.

### Performance Features

- Extended fluid life
- Consistent shifting performance
- Improved shear stability
- Optimised frictional properties
- Excellent wear protection
- Elimination of transmission shudder
- High resistance to oxidation

### Performance Levels

GM: Dexron VI, III(H), III(G), II(E)  
Volvo: 97342  
ZF: TE-ML-09

### Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.846
Kinematic Viscosity @ 40°C	cSt	29.8
Kinematic Viscosity @ 100°C	cSt	6.0
Viscosity Index		151
Flashpoint (Closed)	°C	206
Pour Point	°C	-54
Colour		Red

Figures based on average production values