

## Product Information: Select Motor Oils

### Description

Select Motor Oils are a range of very high-quality detergent free engine lubricants. The products are manufactured utilising highly refined, virgin base oils and carefully selected performance enhancing additives. Select Motor Oils offer excellent protection against wear and corrosion and exhibit outstanding oxidative and thermal stability. These lubricants also offer excellent resistance to foaming and enhanced cold flow characteristics.

### Applications

Select Motor Oils are recommended primarily for use in pre-1960's Veteran; Edwardian; Vintage and Classic cars and commercial vehicles as well as Pioneer; Veteran; Vintage and Classic motorcycles, where a detergent free engine lubricant is preferred or specified. They may also be used in gearboxes where an engine oil is specified, care should be taken to ensure that the correct viscosity is chosen for both engine and gearbox applications.

### Performance Features

- Excellent protection against wear
- Protection against corrosion
- Thermally stable
- Enhanced cold flow characteristics
- Excellent foam control
- Resistant to oxidation

### Performance Levels

API SB

### Typical Data

Characteristic	Unit	SAE 30	SAE 40	SAE 50
Density @ 15.6°C	kg/l	0.872	0.878	0.892
Kinematic Viscosity @ 40°C	cSt	96.0	144.0	224.0
Kinematic Viscosity @ 100°C	cSt	11.2	14.7	19.5
Viscosity Index		102	101	99
Flashpoint (Open)	°C	220	226	230
Pour Point	°C	-30	-24	-19

Figures based on average production values