



## Product Information: STOU 15W-30

### Description

STOU 15W-30 is a universal, multifunctional lubricant intended for use in farm machinery. It is formulated and manufactured using high quality, virgin mineral base fluids which incorporates a tailored additive system, to provide adequate all-round lubrication in various operating systems.

This universal fluid exhibits high anti-wear levels across all systems including gears, as well as providing excellent thermal and oxidation stability and protection against rust and corrosion. The product offers high levels of shear stability and controlled frictional performance to ensure correct clutch and brake operation.

### Applications

STOU 15W-30 is recommended for use in applications where a lubricant of this type and quality is required. These include: engines; transmissions; hydrostatic drives, torque converters, final drives, PTO boxes, brake/clutch systems, hydraulic units, reduction hubs, power steering etc.

### Performance Features

- Allows for reduced inventory
- Eliminates brake squawk and chatter
- Improved gear wear protection
- Rust and corrosion protection
- Low foaming tendency
- Engine soot and wear control
- Good hydraulic response
- Excellent thermal and oxidation stability

### Performance Levels

- API CF-4/SF
- API GL-4
- MB 227.1
- MIL-L-2104D
- Allison C4
- Ford M2C159B
- John Deere J27A
- Massey Ferguson M1135/M1139

### Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	g/ml	0.882
Kinematic Viscosity @ 40°C	cSt	81.1
Kinematic Viscosity @ 100°C	cSt	11.3
Viscosity Index		129
Flashpoint (Closed)	°C	220
Pour Point	°C	-33

Figures based on average production values